


Datasheet	Cartridge preheater	Tmax 65°C
-----------	---------------------	-----------

Features and benefits
<ul style="list-style-type: none"> • Suitable for up to 310 ml cartridges • Self-safe PTC heating element (Tmax 65°C): Prevents uncontrolled heating in the event of a fault • Electronic temperature controller, easily adjustable via three buttons • Carrying strap for easy transport • Silicone-free • EPP housing: Energy-efficient and impact-resistant

Technical data	HC065-C310-230V-R	
	Operating voltage	230 VAC
	Rated power	100 W (@10°C)
	Protection class	I (protective earth)
	IP protection class	IP30
	Housing	EPP
	Weight	1,0 kg
	Connection cable (enclosed) with type F plug	1,5 m
	Dimensions (LxWxH)	250 x 140 x 280 mm

Description
<p>The completely new cartridge preheater was developed for heating up to 310 ml standard cartridges and for use in harsh construction sites and industrial operations. This allows products such as adhesives and sealants to be heated to the optimum processing temperature.</p> <p>Lightweight and resistant to dirt, knocks and drops, it can be transported to the place of use using the carrying strap. Once warmed up, the cartridges retain their temperature for a long time, even without an additional power supply.</p>

Accessories for mobile heating
<p>We also offer an optional inverter (A12V-230V), which can be used to operate the cartridge preheater with 12V. This ensures a constant temperature when traveling in the car.</p>